

## **UN 38.3 TEST SUMMARY REPORT**

## **MSA Corporate Center**

1000 Cranberry Woods Drive Cranberry Township, PA 16066 800.MSA.2222 www.MSAnet.com

October 28, 2019

## Associated MSA Product(s): MSA Responder® PAPR

The attached test summary report has been prepared in accordance with *The UN Recommendations on the Transport of Dangerous Goods, Manual of Test and Criteria, Amendment to the 6<sup>th</sup> Edition, Section 38.3.5 – Lithium cell or battery test summary. The attached summary indicates the successful completion of tests as required in the UN Manual of Tests and Criteria for the lithium metal cell used in the MSA Responder® PAPR. The attached summary applies to all MSA Responder® PAPR lithium ion batteries.* 

The original test summary was provided by the cell manufacturer. A formal request for the original test data shall be made through the manufacturer of the cell.

Sincerely,

David F. Vogt

Dw7Vvt

Global Environmental Program Manager



## **UN 38.3 Test Summary Report**

Lithium Cell or Battery Test Summary in Accordance with Section 2.9.4 UN Model Regulations and Sub-section 38.3 of the UN Manual of Tests and Criteria, Part III, subsection 38.3.5

[a] □ Cell ⊠ Battery □ Product ☑ Tested Type Part #: 37260231 Same Type Part #: 37260226

[b] Manufacturer

Saft Civil Electronics Division

Saft America Inc.

313 Crescent St., Valdese, NC 28690

USA

T: 828-874-4111

lithium-sales@saftbatteries.com https://www.saftbatteries.com/

[d] Unique report ID: 111

[e] Report date: 2002.05.14

[c] Test Laboratory

Saft Civil Electronics Division

Saft America Inc.

313 Crescent St., Valdese, NC 28690

USA

T: 828-874-4111

lithium-sales@saftbatteries.com

https://www.saftbatteries.com/

Same Type Part Numbers # (all): 37260214 37260217 37260226 37260227 37260228 37260229 37260230 37260232 37260234 37260235 37260236 37260237 37260238 37260217 SR181581 ACR:A3-06-2098 Nexergy:10041554 Nexergy:816911

[f] (i) □ Li-ion ⊠ Li-metal.

(iv) Description:BA-5800

Primary (non-rechargeable) Lithium-Sulphur Dioxide (Li-SO2) 2S1P battery. 6.0 Volt, 7.8 Ah.

(ii) Mass:327g.

(iii) ☐ Watt hour rating or ☒ Lithium content; 4.8g.

(v) ☐ Cell 🗵 Battery 🗆 Product. Model number/Part number: 37260231

[g] List of Tests Conducted	Result (Pass / Fail / N.A.)	Test record reference		
38.3.4.1 T.1: Altitude simulation	Pass	5624		
38.3.4.2 T.2: Thermal test	Pass	5624		
38.3.4.3 T.3: Vibration	Pass	5624		
38.3.4.4 T.4: Shock	Pass	5624		
38.3.4.5 T.5: External short circuit	Pass	5624		
38.3.4.6 T.6: Impact/Crush (cell only test)	Pass	5609		
38.3.4.7 T.7: Overcharge (N.A for Li-metal only)	N.A.	N.A.		
38.3.4.8 T.8: Forced discharge (cell only test)	Pass	5609		
[h] Battery assembly: ⊠ Not Applicable. □ UN38	i.3.3 (f) UN38.3.3 (g)			
Iil Test Reference: UN Manual of Tests and Criteria, Part III, sub-section 38.3. Third revised adition 2001				

ria	Test Reference	· HM Manua	of Tacte and	Critoria Dart III	, sub-section 38.3.	Third ro
ш	1 CSt Meletelle	. ON Manua	i oi Tesis anu	Chiena, Part III	, sub-section 38.3.	- i ilii a tev

ised edition 2001/

[j] Signatory A.	Date: 2018.12.27

Name: Casey Fortune

Title: Test Lab Manager

Signature:



	Signato	ry B.	Date:	2018	.12.27	7
--	---------	-------	-------	------	--------	---

Name: Carlos Negrete

Title: Engineering Manager

Signaturé

Important! The above signatory / signatories affirm that this document is a true and correct summary of the original individual tests and test data. The original test data is confidential information available to competent State Authorities with valid identification and only upon their formal request. Disclosure of the original test data to any other entity upon its request will be considered by Saft and, should Saft consider this request is with merit, may be subject to the prior execution of a nondisclosure agreement.